

# VACUUM PUMP

## A3-COMPATIBLE

### Vacuum Pump VP833

Travel light with one pump for A3, A2L and A1

- 8 CFM for fast evacuation
- Works with all common A3, A2L and A1 refrigerants
- Class I, Division 2 Hazardous Locations certified for safe use with flammable A3 refrigerants
- 4 in-line ports for easy hose access and connection
- Rated for 15 microns ultimate vacuum
- Rugged and lightweight with a stable base for easy carry and transport



#### RUNQUICK® OIL CHANGE SYSTEM

The revolutionary RunQuick® Oil Change System allows lightning-fast, 20-second oil changes while the pump is running and without losing vacuum.

Massive, backlit window lets you clearly see the oil condition to maintain peak efficiency.



#### Specifications

<b>Flow Rate:</b>	8 CFM
<b>Port Sizes:</b>	(1) 1/4", (2) 3/8", (1) 1/2"
<b>For Use With:</b>	A3, A2L, and A1 Refrigerants
<b>Not For Use With:</b>	R-702, R-717 Refrigerants
<b>Safety Certification:</b>	Class I, Division 2, Groups A, B, C and D T4 23°F (-5°C) ≤ TAMB ≤ 122°F (50°C)
<b>Ultimate Vacuum:</b>	15 Microns
<b>Compressor:</b>	Rotary Vane, Two Stage
<b>Motor:</b>	3/4 HP Brushless DC, 2500 RPM
<b>Dimensions:</b>	7.9 inch x 11.7 inch x 16.0 inch (201 mm x 296 mm x 406 mm)
<b>Weight Empty:</b>	29 lb / 13 kg
<b>Operating Temperature:</b>	23°F to 122°F (-5°C to 50°C)
<b>Included:</b>	2 x 8oz Vacuum Pump Oil Bottles

