

REVOLUTIONARY RUNQUICK® OIL CHANGE SYSTEM

Clean oil is key for an efficient evacuation and so easy to achieve with the RunQuick® Oil Change System. Monitor oil condition through a large backlit window that is removable for cleaning. Replace oil with the 8 ounce on-board spare in under 20 seconds, while the pump is running, without losing vacuum. Quick, clean, and easy.





Flow Rate, Nominal	10 CFM	8 CFM	6 CFM
Pump Body	EPO Coated aluminum alloy*	Cast iron	Cast iron
Motor	¾ HP DC Motor	¾ HP DC Motor	½ HP AC Motor
Weight	24lbs	27lbs	29lbs
Intake port	4 in-line (1) 1/4", (2) 3/8", (1) 1/2"	4 in-line (1) 1/4", (2) 3/8", (1) 1/2"	4 in-line (1) 1/4", (2) 3/8", (1) 1/2"
RunQuick® Oil Change System	Two 8oz bottles of oil	Two 8oz bottles of oil	Two 8oz bottles of oil
Sturdy base, small footprint	1346 cubic in 15 x 7.8 x 11.5	1346 cubic in 15 x 7.8 x 11.5	1346 cubic in 15 x 7.8 x 11.5
Backlit oil reservoir	Yes	Yes	Yes
Gas ballast	Yes	Yes	Yes
Next Gen Refrigerants	A2L certified	A2L certified	A2L certified