

# CON 600 and CON 610 Meters

**Conductivity, TDS, resistivity, salinity—measure from pure water to seawater!**

**Durable waterproof and dustproof design with IP67 rating** – Even with no probes attached

**Single or multipoint calibration; auto or manual** – Fast, trouble-free calibration for more accurate measurements

**Large backlit graphic display** – Multi-line display with electrode status indicator, calibration data, and more

**User-settable “calibration due” alarm** – Out-of-date or unperformed calibrations are now things of the past!

**Built-in real-time clock** – Time-and-date stamping meets Good Laboratory Practice (GLP) standards

**Advanced data management** – Store up to 500 data sets and download via Infrared IrDA wireless interface

**Set point alarms** – Audible warning when readings are outside set points limit

**Accept 2-cell and 4-cell conductivity probes** – Measure over a broad conductivity range up to 500 mS/cm

**Password protection** – Security for calibration and setup menus

**Rugged rubber boot** – Protects meter from bumps and dings (optional; included with kits)



Rubber boot protects meter in rugged environments

Multiparameter 650-Series meters are available. See pages 57–60.



**3 year warranty**  
meter only

## Specifications

Model	CON 600 meter	CON 610 meter
<b>Conductivity</b>	0 to 200.0 mS	0 to 500.0 mS
<b>TDS</b>	0 to 200 ppt	0 to 500 ppt
<b>Salinity</b>	—	0 to 80 ppt
<b>Resistivity</b>	—	0 to 20.00 MΩ
<b>Temperature</b>	–10.0 to 110.0°C (14.0 to 230.0°F)	–10.0 to 110.0°C (14.0 to 230.0°F)
<b>Resolution</b>	0.05% full-scale; 0.1°C (0.1°F)	
<b>Accuracy</b>	±1% full-scale; ±0.5°C (±0.9°F)	
<b>Calibration</b>	Manual cal, up to 5 points (1 per range); automatic up to 4 points (84.0 μS/cm, 1413 μS/cm, 12.88 mS/cm, 111.8 mS/cm). Temperature offset 0.1°C (0.1°F) increments.	

**TDS factor:** 0.40 to 1.00

**Cell constant:** 0.010 to 10.000

**Memory:** up to 500 sets with GLP date and time

**Output:** infrared, IrDA

**Real-time clock:** time-and-date stamp on calibration and stored data

**Temperature normalization:** 15 or 30°C

**Temperature coefficient:** linear or pure (610 only)

**Temperature compensation:** automatic or manual (selectable) from 0 to 100°C

**Ambient operating temperature:** 0 to 50°C (32 to 122°F)

**Power:** four 1.5 V AA batteries (included) or optional universal AC adapter, up to 200 hours continuous use

**Dimensions**

**Meter:** 7¼”L x 3¼”W x 2¼”H (18.4 x 8.3 x 5.7 cm)

**Boxed:** 9½”L x 9¼”W x 2¾”H (23 x 23 x 7 cm)

**Weight**

**Meter:** 1 lb (0.5 kg); **Boxed:** 2 lb (0.9 kg)

## Ordering Information

Catalog number	Description	Included
WD-35408-02	CON 600 meter only	Meter and batteries
WD-35408-12	CON 610 meter only	Meter and batteries
WD-35408-00	CON 600 meter	Meter, conductivity cell 35408-52, and batteries
WD-35408-10	CON 610 meter	Meter, conductivity cell 35408-52, and batteries
WD-35408-70	CON 600 meter kit	Meter, conductivity cell 35408-52, conductivity standards (60 mL each of four solutions; 1413 μS, 12.88 mS, 3000 ppm, and rinse water), rubber boot, electrode holder, batteries, and hard carrying case
WD-35408-80	CON 610 meter kit	Meter, conductivity cell 35408-52, conductivity standards (60 mL each of four solutions; 1413 μS, 12.88 mS, 3000 ppm, and rinse water), rubber boot, electrode holder, batteries, and hard carrying case

**WD-35408-50 Conductivity cell, 2-electrode, K = 0.1**

**WD-35408-52 Conductivity cell, 2-electrode, K = 1**

**WD-35408-54 Conductivity cell, 2-electrode, K = 10**

**WD-35408-56 Conductivity cell, 4-electrode, K = 0.3**

**WD-35418-83 Optional adapter, 110/220 VAC**

**WD-35418-86 Protective rubber boot for all 600- and 610- series meters**



Laboratory



Industrial



Seawater Testing