

...setting the standard
again and again®

Handheld Meters — pH/Ion

pH/Ion

pH 600 and pH 610 Meters

Expanded range, resolution, and accuracy—plus increased memory and advanced communications!

Durable waterproof and dustproof design with IP67 rating – Even with no probes attached

Push-button pH calibration at up to six points – Up to 15 buffer options with auto-buffer recognition of USA, NIST, DIN, and PWB standards

Large backlit graphic display – Multi-line display with electrode status indicator, calibration data, and more

User-settable “calibration due” alarm – Out-of-date or unperformed calibrations are now things of the past!

Built-in real-time clock – Time-and-date stamping meets Good Laboratory Practice (GLP) standards

Store up to 500 data sets – Infrared IrDA wireless technology makes PC downloading convenient and easy

Set point alarms – Audible warning when readings are outside set points limit

Research-grade accuracy – Resolution to 0.001 pH and accuracy to ± 0.002 pH on pH 610 model

Electrode status indicator – Calibration data provides electrode diagnostic tool

Password protection – Security for calibration and setup menus

Complete kits are available – Include meter, probe, solutions, and carrying case



35418-12

ISO9001:2008
CERTIFIED SUPPLIER



3 year
warranty
meter only

Specifications

Model	pH 600 meter	pH 610 meter
Range	pH	-2.00 to 19.99
	mV	-2000 to 1999
	Temperature	-10.0 to 110.0°C (14.0 to 230.0°F), selectable
Resolution	pH	0.1/0.01 pH
	mV	0.1 mV
	Temperature	0.1°C (0.1°F)
Accuracy	pH	± 0.01 pH
	mV	± 0.2 mV
	Temperature	$\pm 0.5^\circ\text{C}$ ($\pm 0.9^\circ\text{F}$)
Calibration	pH	Up to 6 buffer values (select from 4 sets): USA 1.68, 4.01, 7.01, 10.01, 12.45; NIST: 1.68, 4.01, 6.86, 9.18, 12.45; DIN: 1.09, 2.06, 4.65, 6.79, 9.23, 12.75, or custom buffers
	mV	Offset up to ± 150 mV
	Temperature	Offset 0.1°C (0.1°F) increments

Memory: up to 500 sets with GLP date and time

Output: infrared, IrDA

Real-time clock: time-and-date stamp on calibration and stored data

Temperature compensation: automatic or manual (selectable) from 0 to 100°C

Ambient operating temperature: 0 to 50°C (32 to 122°F)

Power: four 1.5 V AA batteries (included) or optional universal AC adapter, up to 500 hours continuous use

Dimensions

Meter: 7¼" L x 3¼" W x 2¼" H (18.4 x 8.3 x 5.7 cm)

Boxed: 9½" L x 9½" W x 2¼" H (23 x 23 x 7 cm)

Weight

Meter: 1 lb (0.5 kg); **Boxed:** 2 lb (0.9 kg)

Ordering Information

Catalog number	Precalibrated catalog number	Description	Included
WD-35418-02	WD-35418-03	pH 600 meter only	Meter and batteries
WD-35418-12	WD-35418-13	pH 610 meter only	Meter and batteries
WD-35418-00	WD-35418-01	pH 600 meter with probe	Meter, "All-in-One" probe 35816-71, and batteries
WD-35418-10	WD-35418-11	pH 610 meter with probe	Meter, "All-in-One" probe 35816-71, and batteries
WD-35418-70	WD-35418-71	pH 600 meter kit	Meter, "All-in-One" probe 35816-71, pH buffers (60 mL each of 4.01, 7.00, electrode storage solution, and rinse water), two electrode holders, rubber boot, batteries, and hard carrying case
WD-35418-80	WD-35418-81	pH 610 meter kit	Meter, "All-in-One" probe 35816-71, pH buffers (60 mL each of 4.01, 7.00, electrode storage solution, and rinse water), two electrode holders, rubber boot, batteries, and hard carrying case

WD-35816-71 Replacement "All-in-One" pH/temperature probe, single-junction, epoxy body

WD-35816-72 "All-in-One" pH/temperature probe, double-junction, epoxy body

WD-35418-05 ATC probe. Use for temperature compensation with any pH electrode without built-in ATC

WD-35418-83 Optional adapter, 110/220 VAC

WD-35418-86 Rubber boot for all 600-series meters



Ideal for laboratory testing.

Multiparameter
models available.
See pages 51–57.

