

# Multiparameter 35-Series Testrs™

**Our most versatile Testrs combine up to five measurements in one pocket-sized meter**

**Determine pH, conductivity, TDS, salinity, and temperature** – Great for water, wastewater, laboratory, or plant use

**Accuracy up to ±0.01 for pH; ±1% full-scale for EC/TDS/salt** – Ideal for a wide variety of applications

**Long-lasting pH sensor with PVDF reference junction** – Large volume of polymer gel reference gives long, clog-free sensor lifespan

**Stainless steel pin-style conductivity sensors** – Durable and compatible with a wide range of samples

**Adjustable TDS factor, temperature coefficient, and salinity factor** – Provide accurate readings under changing conditions

**Push-button calibration** – Calibrate more precisely than trimpot adjustment; no screwdrivers necessary

**Automatic temperature compensation (ATC)** – Gives you accurate readings even with fluctuating temperatures

**Waterproof, dustproof housing** – Meets IP67 rating, plus it floats!

**Hold function** – Freezes reading until you can record it

**Auto shutoff** – Extends the life of batteries



Sensor includes both pH and conductivity/TDS/salt probes.



## Ordering Information

Catalog number	Description
WD-35425-00	PCTestr 35 (pH/conductivity)
WD-35425-05	PTTestr 35 (pH/TDS)
WD-35425-10	PCSTestr 35 (pH/conductivity/TDS/salt)

## Accessories

**WD-35425-50 Replacement pH/conductivity/TDS/salinity sensor module** for all 35-series Testrs

## Applications

**Water quality:** Hydroponics/agriculture, research labs, industrial process checks, pools, and spas, drinking water, wastewater, aquaculture.

## Specifications

Model	PCTestr 35	PTTestr 35	PCSTestr 35	
Range	pH	0.0 to 14.0 pH	0.0 to 14.0 pH	
	Conductivity	0 to 2000 µS; 2.00 to 20.00 mS	—	0 to 200 µS, 201 to 2000 µS; 2.01 to 20.00 mS
	TDS	—	0 to 1000 ppm; 1.00 to 10.00 ppt	0.0 to 99.9 ppm, 100 to 999 ppm; 1.00 to 10.00 ppt
	Salinity	—	—	0 to 10.00 ppt
	Temperature	0 to 50°C (32 to 122°F)	0 to 50°C (32 to 122°F)	0 to 50°C (32 to 122°F)
Resolution	pH	0.1 pH	0.1 pH	0.01 pH
	Conductivity	10 µS; 0.1 mS	—	0.1 µS, 1 µS; 0.01 mS
	TDS	—	1 ppm; 0.01 ppt	0.1 ppm, 1 ppm; 0.01 ppt
	Salinity	—	—	0.1 ppm, 1 ppm; 0.01 ppt; 0.01%
	Temperature	0.1°	0.1°	0.1°
Accuracy	pH	±0.1 pH	±0.1 pH	±0.01 pH
	Conductivity	±1% full-scale	—	±1% full-scale
	TDS	—	±1% full-scale	±1% full-scale
	Salinity	—	—	±1% full-scale
	Temperature	±0.5°C (±0.9°F)	±0.5°C (±0.9°F)	±0.5°C (±0.9°F)
Calibration	pH	3 points	3 points	5 points
	Conductivity	2 points	—	3 points
	TDS	—	2 points	3 points
	Salinity	—	—	1 point
	Temperature	1 point	1 point	1 point

ISO 9001:2000  
CERTIFIED SUPPLIER



1 year  
warranty  
meter only

**Temperature compensation:** automatic (ATC), from 0 to 50°C (32 to 122°F) or manual  
**Operating temperature:** 0 to 50°C (32 to 122°F)  
**Power:** four 1.5 V alkaline batteries (included), approximately 250 hours continuous use; Eveready® A76 or LR44 equivalent replacement

**Dimensions**  
**Unit only:** 6½" x 1½" dia (16.5 x 3.8 cm)  
**Boxed:** 7¼" x 2½" x 2" (18.4 x 6.4 x 5.0 cm)  
**Weight**  
**Unit only:** 3.25 oz (90 g); **Boxed:** 6 oz (170 g)