




OAKTON[®]
INSTRUMENTS
...setting the standard, again and again[®]

TempTestr[®] IR Food Thermometer 35625-45

Noncontact Food Safety Thermometer














OAKTON[®]
INSTRUMENTS

OAKTON[®]
INSTRUMENTS



HACCP ✓





Temperature Range	Temperaturbereich	Etendue de mesure	Range de Temperatura	Rango de Temperatura	温度範囲	測定温度範囲	-30°C to 205°C (-22°F to 400°F)
Accuracy	Genauigkeit	Precision	Precisão	Precisión	精度	測定精度	Between 0°C and 65°C (32°F to 150°F): ±1°C (±2°F) Below 0°C (32°F): ±1°C (±2°F) ±0.1 degree Above 65°C (150°F): ±1.5% of reading
Assumes ambient operating temperature of 23°C ±2°C (73°F ±4°F)	bei einer Umgebungstemperatur von 23°C ±2K	par 23°C ±2K ambient	Assume a temperatura operacional ambiente de 23°C ±2°C (73°F ±4°F)	Suponiendo Temperatura Ambiente de Operación de 23°C ±2°C (73°F ±4°F)	环境温度为23°C ±2°C 或73°F ±4°F	(23°C ±2°C での値)	
Response Time	Ansprechzeit	Temps de réponse	Tempo de Resposta	Tiempo de Respuesta	响应时间	応答速度	<500ms after initial reading
Spectral Response	Spektrale Empfindlichkeit	Réponse spectrale	Resposta Espectral	Respuesta Espectral	响应波长	応答波長	8-14 microns
Emissivity	Emissionsgrad	Emissivité	Emissividade	Emissividad	发射率	放射率補正	Pre-set for Food Service Applications
Optical Resolution (D:S)	Optische Auflösung (E:M)	Résolution optique (D:S)	Resolução Óptica (D:S)	Resolución Óptica (D:S)	光学分辨率 (D:S)	D:S比	2.5:1 @ 90% energy, typical
Typical Working Range (target illumination)	Typische Messentfernung (Messfleckbeleuchtung)	Distance de mesure classique (Eclairage de la cible)	Range de Operação Típica (iluminação do alvo)	Rango típico de Aplicación (iluminación del objetivo)	典型的工作范围 (目标照明)	標準測定距離	~25mm to 250mm (~1" to 10")
Repeatability	Reproduzierbarkeit	Reproductibilité	Repetibilidade	Repetibilidad	重复性	反復精度	Within accuracy specifications of the unit
Ambient Operating Range	Umgebungstemperaturbereich	Température ambiante	Range Operacional do Ambiente	Temperatura Ambiente de Operación	操作环境温度范围	動作環境温度	0°C to 50°C (32°F to 122°F)
Relative Humidity	Relative Luftfeuchte	Humidité relative	Umidade Relativa	Humedad Relativa	相应湿度	相对湿度	90% (±5%) RH noncondensing @ 30°C (86°F)
Storage Temperature	Lagertemperatur	Température de stockage	Temperatura de Armazenamento	Temperatura de Almacenamiento	储存温度	保存温度	-20°C to 60°C (-4°F to 140°F)
Weight/Dimensions (with battery)	Abmessungen Masse (inklusive Batterien)	Dimensions Masse (avec les piles)	Peso/Dimensões (com bateria)	Peso/Dimensiones (con batería)	重量/尺寸 带(电池)	重量/寸法	150mm x 30mm x 50mm (5.88" x 1.25" x 2") 150g (0.33lbs)
Power	Spannungsversorgung	Alimentation	Alimentação	Alimentación	电源	電源	1 AA alkaline battery
Battery Life	Batterielebensdauer	Autonomie des piles	Durabilidade da Bateria	Duración de la Bateria	电池寿命	電池寿命	10 hours minimum @ 23°C (73°F)
Display Resolution	Anzeigenaufösung	Résolution d'indication de température	Resolução do Display	Resolución en Pantalla	显示分辨率	表示分解能	4 digits, 0.2°C (0.5°F)
Display Hold	Anzeigenhaltezeit	Durée d'affichage	Espera do Display	Retención de Lectura	显示保持	ホールド時間	7 sec
Standards	Standards	Standards	Padrões	Estándares	标准	適合規格	Conforms to: • EN61326-1 Electromagnetic Emissions and Susceptibility, Criteria B • EN61010-1 General Safety
Environmental Sealing	Schutzgrad	Degré de protection	Vedação Ambiental	Sellado Ambiental	环境密封	保護等級	IP54 Sealing (hand washable, non-submersible)
Minimum Target Size	Kleinste Messfleckgröße	Taille minimale du spot	Tamanho Mínimo do Alvo	Tamaño Mínimo de Objetivo	最小目标尺寸	最小スポットサイズ	~12mm (~0.5")