

pHTestrs® 10, 20, and 30

Easier measurements with more information from a larger display

Unique double-junction electrode design

Longer electrode life, especially in harsh applications like wastewater, plating baths, life science, and food

Waterproof, dustproof housing – IP67 rated, maintains the integrity of your tester even in dirty or damp field conditions. Plus, it floats!

Replaceable electrode module – Reuse the same meter body for cost savings

Push-button calibration with auto-buffer recognition

Automatic temperature compensation (ATC) – Accurate readings even with fluctuating temperatures

Hold function – Freezes reading so that you can record it

Self-diagnostic error messages – Make troubleshooting easier

Auto shutoff – Extends the life of the batteries

pHTestr 10 features – Three-point calibration, ±0.1 pH accuracy

pHTestr 20 features – Three-point calibration, ±0.01 pH accuracy

pHTestr 30 features – Three-point calibration, ±0.01 pH accuracy, and simultaneous temperature display



35634-30
Waterproof
double-junction
pHTestr 30



ISO 9001:2008
CERTIFIED SUPPLIER



1 year
warranty
meter only

Specifications

Model	pHTestr 10	pHTestr 20	pHTestr 30
Range	–1.0 to 15.0 pH	–1.00 to 15.00 pH	–1.00 to 15.00 pH
Resolution	0.1 pH	0.01 pH	0.01 pH
Accuracy	±0.1 pH	±0.01 pH	±0.01 pH
Temperature display	—	—	0 to 50°C (32 to 122°F)
Calibration	Three point at either pH 4.0, 6.86/7.0, or 9.18/10.0		

Temperature compensation: automatic (ATC), from 0 to 50°C (32 to 122°F)

Operating temperature: 0 to 50°C (32 to 122°F)

Special functions: On/Off or Auto-Off after 8.5 minutes; Hold; Calibrate and Confirm

Power: four 1.5 V alkaline batteries (included), >500 hours continuous use; Eveready® A76 or LR44 equivalent replacement

Dimensions

Unit only: 6½" x 1½" dia (16.5 x 3.8 cm)

Boxed: 7¼" x 2½" x 2" (18.4 x 6.4 x 5.0 cm)

Weight

Unit only: 3.25 oz (90 g); **Boxed:** 4.5 oz (125 g)

Ordering Information

Catalog number	Description	Included
WD-35634-10	pHTestr 10	Tester, detachable electrode sensor, and batteries
WD-35634-20	pHTestr 20	Tester, detachable electrode sensor, and batteries
WD-35634-30	pHTestr 30	Tester, electrode, detachable electrode sensor, calibration buffer pouches, and batteries

Accessories

WD-35624-38 Replacement electrode sensor for pHTestr 10, 20, and 30

WD-35634-70 pHTestr 10 calibration kit includes Testr, calibration buffer pouches (two each of pH 4.01, 7.00, 10.00 and rinse water), sample jar, and sturdy carrying case

WD-35634-80 pHTestr 20 calibration kit includes Testr, calibration buffer pouches (two each of pH 4.01, 7.00, 10.00 and rinse water), sample jar, and sturdy carrying case

WD-35634-90 pHTestr 30 calibration kit includes Testr, calibration buffer pouches (two each of pH 4.01, 7.00, 10.00 and rinse water), sample jar, and sturdy carrying case



All Oakton® waterproof pHTestrs float!



Large LCD