
#### **SPECIFICATIONS**

Temperature Range: -40 to 482°F Resolution: 0.1° Accuracy: ± 0.9°F from -4 to 482°F, otherwise

Response Time: 2 seconds within 1 degree Calibrated: 40°F and 140°F Battery: CR2032 3V button cell

### **GETTING STARTED**

Extend probe and thermometer is ready to use.



#### DESCRIPTION (FRONT)

- 1. Probe 18/8 stainless-steel
- 2. Food Safe Antimicrobial coating
- 3. 2 inch LCD
- 4. Opening for lanyard

#### SWITCHING BETWEEN C°/F°

Using the C°/ F° switch found inside battery compartment, toggle between Celsius and Fahrenheit. Simply twist open battery cover and remove battery to access switch.



# DESCRIPTION (BACK)

- 1. Battery compartment
- 2. Probe compartment
- 3. Magnetic back

Thermometer will automatically enter sleep mode after 60 seconds. Simply retract and extend probe to exit sleep mode and continue use.

# MAGNETIC BACKING

Unit has a built-in magnetic backing to allow for convenient storage. Magnetic backing may not work on stainless steel surfaces.

#### SPLASH RESISTANT

Thermometer is rated at IP65 splash resistance. It is protected against low pressure jets if water, such as splashes from a tap.

#### TAPERED SENSOR TIP

The ultra-sensitive thermistor sensor is located at the tip of the probe, requiring a minimum insertion distance of 0.25 inches (5 mm).

#### ANTIMICROBIAL COATING

Silver-based antimicrobial additive is impregnated into the plastic shell to inhibit the growth of pathogens. Efficacy is rated at 99% or greater.

### TROUBLESHOOTING

WON'T SWITCH ON:

Retract and extend probe or change battery

DISPLAYING "ERROR":

Battery needs to be replaced soon.

# DEVICE ASLEEP:

Retract and extend probe.


## USE & MAINTENANCE

· Always measure at center of meat, avoid hitting bone or hard cartilage.

- · Prevent build up of grime; always clean the body with soft damp cloth.
- Do not clean with solvents or scouring agents.
- Do not put device in dishwasher.
- Do not leave device in oven.
- · Do not place probe directly over fire.
- Do not immerse device for any length of time.
- · Do not subject device to extreme temperature, vibration, or shock.

#### REPLACING BATTERY

When display shows "ERROR", it's time to change the battery. Fully retract probe and twist open the battery door with a coin. Carefully remove existing battery and insert a new CR2032 with the positive (+) pole up.



# FOOD TEMPERATURE GUIDE

Recommended Meat Temperatures

Meat	Rare	Med. Rare	Medium	Med. Well	Well Done
Beef, Veal & Lamb	115°F 46°C	125°F 52°C	135°F 57°C	145°F 63°C	155°F 68°C
Pork	Х	125°F 52°C	130°F 54°C	135°F 57°C	140°F 60°C
Salmon & Other Fatty Fish	Х	115°F 46°C	125°F 52°C	135°F 57°C	145°F 63°C
Sea Bass & Other Lean Fish	Х	125°F 52°C	130°F 54°C	135°F 57°C	140°F 60°C
Shellfish	120°F 49°C	Х	130°F 54°C	Х	140°F 60°C

NOTE: These are common temperatures used by professional chefs to achieve a desired taste and texture. For USDA recommended doneness, add on another 5 to 10°F (2 to 5°C). Please also be aware that internal temperature will continue to rise as your dish is resting.

#### ADDITIONAL TEMPERATURES FOR SAFETY

Meat	Safe Temperature
Ground Meat	160°F / 71°C
Ham (raw)	160°F / 71°C
Ham (smoked)	140°F / 60°C
Poultry	165°F / 74°C
Brisket, Pork Ribs, Shoulders	190-205°F / 88-96°C
Sausage	160°F / 71°C

Candy Temperatures			
Thread	230-234°F / 110-112°C		
Softball	234-240°F / 112-116°C		
Firmball	244-248°F / 118-120°C		
Hardball	250-266°F / 121-130°C		
Soft Crack	270-290°F / 132-143°C		
Hard Crack	300-310°F / 149-154°C		
Caramel	320-350°F / 160-I77°C		

TRACEABLE® 2 SECOND-TEMP™ NSF FOOD **CERTIFIED THERMOMETER** INSTRUCTIONS