



WT-30

Salinity Pen-Type Water Quality Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with these easy to use, one touch water management testers. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- Measures Salinity from 1.0 to 70.0 ppt (NaCL)
- Dual LCD display with salinity and temperature (selectable C and F)
- Waterproof and dustproof - IP65
- Quick response time
- Easy to calibrate
- Built-in NaCL temperature coefficient
- Built-in NaCL conductivity to TDS conversion factor
- Data hold
- Pen size, easy to fit in pocket
- Low battery indicator
- Auto power-off disable
- Simple one-touch auto-calibration
- Easy One-touch, multi point calibration

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



WT-30 Salinity Pen-Type Water Quality Meter

Data Sheet

Specifications

Salinity Range	0.00 ~ 10.00, 10.1 ~ 70.0 ppt
Resolution	0.01ppt / 0.1ppt
Accuracy	±1% Full Scale ±1 dgt
Normalization	Fixed at 25°C (77°F)
Waterproof Rating	IP 65
Temperature compensation	0°C to 50°C (32°F to 122°F)
Temperature coefficient	Built-in NaCL Temperature coefficient
Operating Temperature	0°C to 50°C (32°F to 122°F)
Power Requirements	4x1.5V batteries (Type A76 or LR44)
Auto Power Off	20 minutes after last key op
Dimension	165 x 35 x 32mm (6.5 x 1.4 x 1.3 in)
Weight	Approx. 56g (0.12 lb)

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved.
7/2009 3520495 Rev A