



## WT-80 PH / ORP Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with this easy to use, one touch water management tester. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- Used to check pH or ORP in water testing and treatment applications
- Dual LCD display with pH / mV and temperature (selectable C and F) (Temperature probe is optional accessory)
- USB port for data download to a PC (cable & software optional)
- Backlight display for use in dark areas
- pH electrode with Automatic Temperature Compensation for measurement accuracy
- 3 points pH calibration with automatic buffer recognition to prevent calibration errors
- Data Hold
- Max/Min and Data Recording
- Low bat indicator
- Auto power off
- Applications include : Pools, Spas, Aquariums, Labs, Aquaculture, Sanitation plants, Car washes, Hydroponics, Water & Wastewater treatment and Boilers / Steam generator maintenance

### No hassle warranty

*No waiting.*

*No shipping  
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



## WT-80 pH / ORP Meter

## Data Sheet

### Specifications

|                               |                                                                                               |
|-------------------------------|-----------------------------------------------------------------------------------------------|
| pH Range                      | 0.00~14.00                                                                                    |
| with High Resolution          | 0.01pH                                                                                        |
| pH Accuracy                   | ±0.02pH                                                                                       |
| mV Range                      | -199.9 ~ +199.9mV, -1999 ~ +1999mV                                                            |
| mV Resolution                 | 0.1mV( -199.9~+199.9 ) or 1mV (-1999~+1999 )s                                                 |
| mV Accuracy                   | ±0.2mV( -199.9~+199.9 ) or ±2 mV (-1999~+1999 )                                               |
| Temp. compensation (pH probe) | -5°C to 80°C (23°F to 176°F)                                                                  |
| Accuracy (pH probe)           | ±0.3°C (± 31.5°F to 32.5°F)                                                                   |
| Operating Temperature         | 0°C to 50°C (32°F to 122°F), Max.80%RH                                                        |
| Power Requirements            | 4x1.5V batteries AAA                                                                          |
| Dimension                     | 175 x 70 x 33 mm (6.9 x 2.8 x 1.3 in)                                                         |
| Weight                        | Approx. 157g (0.35 lb)                                                                        |
| Package Contains              | Meter, Battery, Instruction manual, Carrying Pouch, pH probe, ORP probe, pH standard solution |
| Accessories                   | TPK-60                                                                                        |

### Amprobe® Test Tools

website: [www.Amprobe.com](http://www.Amprobe.com)  
email: [info@amprobe.com](mailto:info@amprobe.com)  
Everett, WA 98203  
Tel: 877-AMPROBE

### Amprobe® Test Tools Europe

In den Engematten 14  
79286 Glottertal, Germany  
Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved.  
7/2009 3520549 Rev A