

Part No.

XTHP-KIT2

XTHP hydraulic pump, 3 gauge adapters - (1/4" MNPT, 1/8" MNPT, 1/4" FNPT), 3ft hose, zippered bag, carrying case

Calibration kit with pump, 3 gauge adapters, hose, carrying case



XTHP-KIT2

Included Items

- Hand Pump - XTHP Hydraulic Pump (XTHP)
- Reference Connection - Kit containing 1/8" MNPT, 1/4" MNPT, 1/4" FNPT stainless steel Quick-test XT adapters (XTHA-KIT3)
- Process Connection - 1/4" male NPT x male Quick-test XT Adapter, S.S. (XTHA-2MS0)
- Hose - Quick-test XT 10,000 psi hose, S.S. hose ends, 3ft long (XTXT-HOS-3ft)
- Case - QTHP, XTHP Hand Pump Carrying Case (QTHP-0275)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

Hand Pump XTHP

Materials	Anodized Aluminum, Stainless Steel, Delrin, Polysulfone
Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Mineral Oil, Petroleum Based Oil, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil
Seal Materials	Teflon, Viton
Outlet Port	Male Quick-test XT, Male Quick-test XT with cap and chain
Pressure Media	Liquid
Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Reservoir Volume	4.2 fl. oz
Fine Adjustment Resolution	0.01 PSI / 0.07 mbar / 0.00 kPa
Max Operating Temperature	140 °F / 60 °C
Harmonized Code	8413.20.0000

Hand Pump XTHP

Country of origin	USA
Min Operating Temperature	-15 °F / -26 °C
Weight	3.12 lbs / 1.41 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 7.5 in (19.05 cm) x D: 10.6 in (26.92 cm)

Reference Connection XTHA-KIT3

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Min Operating Temperature	0 °F / -18 °C
Wrench Size	9/16, 3/4 In 15, 19 mm

Process Connection XTHA-2MSO

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Teflon, Viton
Wrench Size	5/8 In 16 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test XT
Dimensions	H: 1.29 in (3.28 cm) x W: 0.63 in (1.6 cm)

Hose XTXT-HOS-3ft

Burst Pressure	40000 PSI / 2760 bar / 275 MPa
Color	Blue
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Reinforced Polyamide, Stainless Steel
Max Operating Temperature	140 °F / 60 °C

Hose XTXT-HOS-3ft

Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.24 In / 7.00 mm
Type	XT

Case QTHP-0275

Impact Resistance	MIL-STD-3010C
Ingress Protection	IP67 (1 meter water submersion for 30 minutes), MIL-STD-810F
Materials	ABS Plastic, Polyethylene foam
Weight	8.00 lbs / 3.63 kg
Dimensions	H: 14.9 in (37.85 cm) x W: 12.1 in (30.73 cm) x D: 9.6 in (24.38 cm)

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6 in (15.24 cm) x W: 1 in (2.54 cm) x D: 7 in (17.78 cm)